

**PROFIED SPACER FOR INSULATION GLAZING ASSEMBLY**

**Patent number:** WO9915753  
**Publication date:** 1999-04-01  
**Inventor:** BRUNNHOFER ERWIN (DE); GOER BERNHARD (DE);  
 REGELMANN JUERGEN (DE)  
**Applicant:** CAPRANO & BRUNNHOFER (DE); BRUNNHOFER  
 ERWIN (DE); GOER BERNHARD (DE); REGELMANN  
 JUERGEN (DE)

**Classification:**

- international: **E06B3/663; E06B3/66;** (IPC1-7): E06B3/663

- european: E06B3/663B2B; E06B3/663B8

**Application number:** WO1998DE02470 19980818

**Priority number(s):** DE19981005265 19980210; DE19971042531 19970925

**Also published as:**

EP1017923 (A1)  
 US6339909 (B1)  
 DE19805265 (A1)  
 CA2304291 (A1)  
 EP1017923 (B1)

more >>


**Cited documents:**

DE7831818U  
 GB2162228  
 EP0601488

[Report a data error here](#)

**Abstract of WO9915753**

The present invention relates to a profiled spacer for a spacing frame which is placed in the edge area of an insulation glazing assembly for forming an intermediate spacing between window panes. Said spacer comprises a chamber (10) for receiving hygroscopic materials and having at least one support leg (30, 36) resting on the inner surface of the pane at least on one side of said chamber, wherein said leg is connected to the chamber by a bridge section (32, 34). This profiled spacer is characterised in that its profiled body is made of a low thermal conductivity material capable of resilient and plastic deformation. The support leg at least is further connected by material connection to a reinforcing layer (40) capable of plastic deformation.



Data supplied from the **esp@cenet** database - Worldwide